

AirTalk® ZETA

Product information

The new On-The-Ear variant for integration into the AirTalk® family.

- Versatile compatible On-The-Ear headset solution
- Sleek and Stylish Design
- Advanced Audio Quality with acoustic components from the AirTalk® 5000
- Flexible gooseneck microphone for best transmission
- Splitting(Stereo) or mono version for all user scenarios
- Fully adaptable to the AirTalk® PTT units



TECHNICAL BASICS

GENERAL INFORMATION

Dimensions (L x W x H)	180 mm x 140 mm x 65 mm
Dimensions cushions (D)	65 mm
Colour	black/ blue metallic
Weight	116 g
Operation temperature	-20 °C to + 40 °C
Noise Cancelling (NC)	YES
Calm Noise Line (CNL)	YES
Acoustic Shock Protection	YES

SPEAKER

Working principle	Dynamic
Impedance	600 Ω ± 20 % (1 kHz)
Sensitivity	107 dB ± 3 dB (1 mW)
Frequency range	100 Hz to 12 kHz

MICROPHONE

Working principle	Electret
Direction	Bi - directional
Impedance	1,5 kΩ ± 30 % (1 kHz)
Frequency range	100 Hz to 7 kHz
Sensitivity	-47 dB ± 3,5 dB (1 kHz)
Sound pressure level	110 dB (S. P. L.)
Distortion	57 dB (1 kHz)

TD-AIRTALK_ZETA-A-032024-EN